

Pool Magnet Plus



Brand: Bioguard

Product Code: 23454BIO

Availability: In Stock

Weight: 0.00oz

Dimensions: 0.00ft x 0.00ft x 0.00ft

Price: \$25.99

Description

1 Quart - Pool Magnet Plus

What it does

BioGuard® Pool Magnet® Plus is a concentrated chelating agent that ties up metals (iron, copper and manganese). This product removes fresh stains and prevents staining due to metals. Use this product monthly for swimming pools with metal containing fill water.

Features

- 15 - 40% etidronic acid
- 0.5 - 1.5% phosphonic acid
- pH <3.5
- Concentrated formula
- Compatible with chlorine, bromine, Mineral Springs®, and saltwater systems
- Do not use with SoftSwim® or other biguanide systems

Benefits

- Prevents stains caused by metals
- Removes fresh metal stains
- Easy to apply

Directions for Use

Directions for Use

Prevention of Stains

1. Backwash the filter, then allow the pump to run continuously.
2. Apply 1 quart of Pool Magnet[®] Plus per 10,000 gallons for every 1.0 ppm metals. Maximum recommended dose is 3 qts. per 10,000 gallons. If staining is present, add product directly over these stains.
3. If the total amount of metals present exceeds 1.0 ppm, apply Sparkle Up[®] Filter Aid 48 hours after Pool Magnet[®] Plus addition to assist in metal removal.

Temporary clouding may occur upon addition.

Removal of Fresh Stains

1. Turn the pump off for 8 hours.
 2. Slowly and as close to the surface of the water as possible, pour one to three (depending on severity of stains) quarts of Pool Magnet[®] Plus directly in the area of the stain.
 3. Do not swim or operate pump for 24 hours.
 4. After the waiting period, turn the pump back on to circulate the water and brush the pool daily for 5-7 days.
 5. Use BioGuard[®] Sparkle Up[®] in the filter to aid in the removal of redissolved metals.
- For Iron staining, use Erase[®] Iron Stain Remover in conjunction with Pool Magnet[®] Plus. Follow Erase[®] Iron Stain Remover label instructions.
 - For white plaster pools (only) where large metal stains have aged into the pools surface, draining and acid washing is recommended.

Maintenance Dose

- When fill water contains metals, add 3 oz. of Pool Magnet[®] Plus per 1,000 gallons of water added to the pool.